

TIMBEREX INTERNATIONAL LIMITED

WATCO HOUSE, FILMER GROVE, GODALMING, SURREY GU7 3AL

TEL: 01483 425 000 FAX: 01483 418 888

MATERIAL SAFETY DATA SHEET

PAGE: 1/3

REVISION (3): 20/10/05

1 PRODUCT NAME: Timberex Free

2 CHEMICAL COMPOSITION:

	∞ Modified natural oil blend (100% solids)			
	HAZARDOUS COMPONENTS	Wt%	Symbol	R Phrases
43	Cobalt zirconium carboxylate	<0.5%	Xi	38,
	Methyl ethyl ketoxime	<0.5%	Xn	21, 40,41,43

3 HAZARDS IDENTIFICATION: None known, but see section 16. Will burn in a fire.

4 FIRST AID MEASURES:

- 4.1 General Advice: Remove contaminated clothing. Launder before re-use.
- 4.2 Inhalation: Significant inhalation unlikely. If in doubt remove patient to fresh air.
- 4.3 Eye Contact: Rinse with copious amounts of water and seek immediate medical attention.
- 4.4 Skin Contact: Remove surplus material, then wash with soap and water.
- 4.5 Ingestion: Rinse out mouth with water. Do not induce vomiting. Consult a doctor.

5 FIRE PRECAUTIONS:

- 5.1 Extinguishing Media: CO₂, foam, dry chemical
- 5.2 Extinguishing Media NOT to be used: Water
- 5.3 Product Combustion Hazards: Smoke, CO, CO₂
- 5.4 Special Protective Equipment for Firefighters: -

6 SPILLAGE:

- 6.1 Personal Precautions: Avoid skin and eye contact.
- 6.2 Environmental Precautions: -
- 6.3 Removal of Spillage: Absorb in earth or sand and transfer to suitable container for disposal.
- 6.4 Further Advice: -

7 HANDLING & STORAGE:

- 7.1 Safe Handling: It is recommended that gloves and safety goggles are worn.
- 7.2 Safe Storage: Store in closed containers in dry, cool conditions.

PRODUCT: *TIMBEREX FREE*

PAGE: 2/3

REVISION (3): 20/10/05

8 PERSONAL PROTECTION:

- 8.1 Respiratory Protection: Good ventilation in working areas recommended.
- 8.2 Hand Protection: Oil resistant gloves. Seek advice from glove suppliers and follow their instructions.
- 8.3 Eye Protection: Safety glasses recommended.
- 8.4 Skin Protection: Industrial clothing.

9 PHYSICAL & CHEMICAL PROPERTIES:

- 9.1 Appearance: Liquid
- 9.2 Odour: Mild
- 9.3 Colour: Brown
- 9.4 Boiling Point/Range: >200^oC
- Flash Point: >260^oC
- Auto Ignition Temp: -
- Oxidising Properties: -
- Relative Density: <1.0 g / c.c.
- Melting Point/Range: -
- Flammability(solid, gas): -
- Explosive Limits: -
- Vapour Pressure: -
- Water Solubility: Insoluble
- Volatile Organic Content: <0.5%

10 STABILITY & REACTIVITY:

- 10.1 Conditions to avoid: Heat, sources of ignition
- 10.2 Materials to avoid: Oxidising agents
- 10.3 Hazardous Decomposition Products: CO, CO₂, smoke

11 TOXICOLOGICAL INFORMATION:

There is no data available on the product itself. The product has been assessed following conventional method in CHIP and is classified for toxicological hazards accordingly. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. See Sections 3 and 15 for details of the resulting hazard classification.

12 ECOLOGICAL INFORMATION:

Prevent contamination of soil, drains or surface water.
This preparation has been assessed following the conventional method in CHIP and is classified for ecological effects accordingly. See Sections 3 and 15 for details.

13 SAFE DISPOSAL:

- 13.1 Product: Dispose of by controlled incineration.
- 13.2 Container: Dispose of by controlled incineration.

PRODUCT: TIMBEREX FREE

PAGE: 3/3

REVISION (3): 20/10/05

14 **TRANSPORT INFORMATION:** Not classified as hazardous for transport

15 **REGULATORY INFORMATION:** Not classified as hazardous for supply

R phrases

- -

S phrases

Other Data: Contains Methyl Ethyl Ketoxime and Cobalt Zirconium Carboxylate. May produce an allergic reaction.

16 **OTHER INFORMATION:** Under certain conditions, applicators, cloths, sawdust, etc.,
impregnated with this product can spontaneously combust. To prevent the
possibility of spontaneous combustion impregnated applicators, cloths, sawdust,
etc., should be immediately placed in a metal container filled with water,
sealed and placed outside the building. The container should then be
disposed of according to local regulations.