

TIMBEREX INTERNATIONAL LIMITED

WATCO HOUSE, FILMER GROVE, GODALMING, SURREY GU7 3AL

TEL: 01483 425 000

FAX: 01483 428 888

MATERIAL SAFETY DATA SHEET

PAGE: 1/ 3

REVISION (): 30/05/02

1 PRODUCT NAME: Hardwood Lut – All Grades

2 CHEMICAL COMPOSITION:

	CAS No.	Wt%	Symbol	R Phrases
Oxalic Acid	144-62-7	5.0%	Xn	21/22

3 HAZARDS IDENTIFICATION: May irritate eyes and respiratory system.

4 FIRST AID MEASURES:

- 4.1 General Advice: -
- 4.2 Inhalation: Remove patient to fresh air. Seek medical advice if symptoms persist.
- 4.3 Eye Contact: Flush with water. Seek medical attention.
- 4.4 Skin Contact: Rinse with plenty of water.
- 4.5 Ingestion: Wash mouth with water. Do not induce vomiting. Give water to drink and seek medical attention.

5 FIRE PRECAUTIONS:

- 5.1 Extinguishing Media: -
- 5.2 Extinguishing Media NOT to be used: -
- 5.3 Product Combustion Hazards: CO, carbon dioxide.
- 5.4 Special Protective Equipment for Firefighters:-

6 SPILLAGE:

- 6.1 Personal Precautions: -
- 6.2 Environmental Precautions: -
- 6.3 Removal of Spillage: Absorb onto earth or sand and place in suitable container. Flush residues with plenty of water.
- 6.4 Further Advice: Floor area may be slippery.

PRODUCT: HARDWOOD LUT – ALL GRADES

PAGE: 2/ 3

REVISION (): 30/05/02

7 HANDLING & STORAGE:

- 7.1 Safe Handling: Wear gloves. Avoid contact with skin and eyes.
- 7.2 Safe Storage: Store in a closed container at ambient temperature.

8 PERSONAL PROTECTION:

- 8.1 Respiratory Protection: Not required.
- 8.2 Hand Protection: Not required.
- 8.3 Eye Protection: Safety glasses.
- 8.4 Skin Protection: Not required.

9 PHYSICAL & CHEMICAL PROPERTIES:

- 9.1 Appearance: Liquid
- 9.2 Odour: Minimal
- 9.3 Colour: As described.
- 9.4 Boiling Point/Range: Approx. 100Y C
- Flash Point: -
- Auto Ignition Temp: -
- Oxidising Properties: -
- Relative Density: 1.02 to 1.1.
- Melting Point/Range: >0 C
- Flammability(solid, gas): -
- Explosive Limits: -
- Vapour Pressure: -
- Water Solubility: Soluble
- Other Data: -
- Solvent Content: Nil

10 STABILITY & REACTIVITY:

- 10.1 Conditions to avoid: Normally stable.
- 10.2 Materials to avoid: Strong oxidisers, strong acids and bases.
- 10.3 Hazardous Decomposition Products: CO, carbon dioxide, formic acid.

11 TOXICOLOGICAL INFORMATION:

- 11.1 Toxicity: LD50 Oral: 7500mg/kg.
- LD50 Skin: -
- Skin Irritation: -
- Sensitisation: -
- Inhalation: -
- Recommended Exposure Limit: -

12 ECOLOGICAL INFORMATION: Readily biodegradable.

PRODUCT: HARDWOOD LUT – ALL GRADES

PAGE: 3/3

REVISION (): 30/05/02

13 **SAFE DISPOSAL:**

13.1 Product: Dispose of with respect to local Byelaws.

13.2 Container: Not classed as hazardous waste.

14 **TRANSPORT INFORMATION:** Not classified as hazardous for transport

15 **REGULATORY INFORMATION:** Not classified as hazardous for supply.

R phrases

S phrases

2: Keep out of the reach of children.

24/25: Avoid contact with skin and eyes.

Other Data:

16 **OTHER INFORMATION:** -