

TIMBEREX INTERNATIONAL LIMITED

WATCO HOUSE, FILMER GROVE, GODALMING, SURREY GU7 3AL

TEL: 01483 425 000 FAX: 01483 418 888

MATERIAL SAFETY DATA SHEET

PAGE: 1/3

REVISION (4): 20/10/05

1 PRODUCT NAME: Satin Oil Gold Mousse

2 CHEMICAL COMPOSITION: Long oil alkyd blend in Aerosol form.

Hazardous Components		Wt%	Symbol	R Phrases
Distillate (petroleum) Hydrogen treated, light	CAS 64742-47-8 EC 265-149-8	10-20%	Xn	65, 66
Hydrogenated Castor Oil	CAS 61788-85-0	5-10%	-	-
Cobalt zirconium carboxylate 38,43			<0.5% Xi	
Methyl ethyl ketoxime		<0.5%	Xn	21,40,41,43
1, 1, 1, 2 Tetrafluoroethane (HFC 134a)	CAS 811-97-2	5-10%	-	-

3 HAZARDS IDENTIFICATION: May be harmful when inhaled after frequently repeated exposure. Drying of the skin.

4 FIRST AID MEASURES:

4.1 General Advice:	-
4.2 Inhalation:	Remove to fresh air and rest.
4.3 Eye Contact:	Rinse with water and consult a doctor if problems persist.
4.4 Skin Contact:	Remove splashed clothes. Wash skin with soap and water.
4.5 Ingestion:	Drink milk or water to dilute the product. Do not induce vomiting.

5 FIRE PRECAUTIONS:

5.1 Extinguishing Media:	CO ₂ , foam, dry chemical.
5.2 Extinguishing Media <u>NOT</u> to be used:	Water jet.
5.3 Product Combustion Hazards:	Smoke, CO, CO ₂
5.4 Special Protective Equipment for Firefighters:	Use smoke immersion equipment when extinguishing fires as protection against toxic and irritant gases.
5.5 Special Risks: during	Smoke hazardous to health is formed fires.

6 SPILLAGE:

6.1 Personal Precautions:	Use chemical resistant gloves and boots.
6.2 Environmental Precautions: In	Prevent leakage of large quantities into the drainage system. the event of larger spills contact with emergency services.
6.3 Removal of Spillage:	Absorb in earth or sand and transfer to suitable container for disposal.
6.4 Further Advice:	-

PRODUCT: SATIN OIL GOLD MOUSSE

PAGE: 2/3

REVISION (4): 20/10/05

7 HANDLING & STORAGE:

- 7.1 Safe Handling: It is recommended that gloves and safety goggles are worn.
- 7.2 Safe Storage: Store in closed containers in dry, cool conditions. Avoid sources of ignition and direct sunlight. Containers must not be exposed to temperatures above 50 C.

8 PERSONAL PROTECTION:

- 8.1 Respiratory Protection: Ensure good ventilation in working areas.
- 8.2 Hand Protection: Solvent resistant gloves. Seek advice from glove suppliers and follow their advice.
- 8.3 Eye Protection: Safety glasses recommended.
- 8.4 Skin Protection: Industrial clothing.

9 PHYSICAL & CHEMICAL PROPERTIES:

- 9.1 Appearance: Liquid
- 9.2 Odour: Weak
- 9.3 Colour: Yellow
- 9.4 Boiling Point/Range: >200 C
- Flash Point: 101 C
- Auto Ignition Temp: -
- Oxidising Properties: -
- Relative Density: <1.0
- Melting Point/Range: -
- Flammability(solid, gas): -
- Explosive Limits: -
- Vapour Pressure: -
- Water Solubility: Insoluble
- Other Data: -
- Solvent Content: -

10 STABILITY & REACTIVITY:

- 10.1 Conditions to avoid: Avoid excessive heat and sources of ignition.
- 10.2 Materials to avoid: Reacts with strong oxidants.
- 10.3 Hazardous Decomposition Products: When burned forms smoke, carbon oxides and other toxic and irritant gases (hydrogen fluoride and phosgene).

11 TOXICOLOGICAL INFORMATION:

- 11.1 Toxicity: LD50 Oral: -
- LD50 Skin: -
- Skin Irritation: Degreases the skin which can result in redness, cracked skin and, in the event of long term or repeated contact, eczema (non-allergic).
- Sensitisation: -
- Inhalation: High contents of vapour can cause headaches, dizziness, tiredness and nausea.
- Recommended Exposure Limit: No limit set for solvent, but 300ppm recommended.

PRODUCT: SATIN OIL GOLD MOUSSE

PAGE: 3/3

REVISION (4): 20/10/05

12 ECOLOGICAL INFORMATION:

Prevent contamination of soil, drains or surface water.
This preparation has been assessed following the conventional method in CHIP and is not classified as dangerous for the environment.

13 SAFE DISPOSAL:

13.1 Product: Dispose of by controlled incineration.

13.2 Container: Dispose of by controlled incineration.

14 TRANSPORT INFORMATION:

ADR	UN1950	Class 2	Aerosols
IMDG	UN1950	Class 2	Aerosols

15 REGULATORY INFORMATION:

Other Data: Pressurised container. Must not be exposed to direct sunlight or temperatures above 50 C. Must not be punctured or burned. This also applies to the empty container.

Contains methyl ethyl ketoxime and cobalt zirconium carboxylate. May cause an allergic reaction.

16 OTHER INFORMATION:

Under certain conditions, applicators, cloths, sawdust, etc., impregnated with this product can spontaneously combust. To prevent the possibility of spontaneous combustion impregnated applicators, cloths, sawdust, etc., should be immediately placed in a metal container filled with water, sealed and placed outside the building. The container should then be disposed of according to local regulations.

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation. It provided guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.