

TIMBEREX INTERNATIONAL LIMITED

WATCO HOUSE, FILMER GROVE, GODALMING, SURREY GU7 3AL

TEL: 01483 425 000 FAX: 01483 418 888

MATERIAL SAFETY DATA SHEET

PAGE: 1/3

REVISION (2): 05/08/03

1 PRODUCT NAME: Satin Oil Gold

2 CHEMICAL COMPOSITION:

- Long oil alkyd blend (80% solids)

Hazardous Components	CAS	Wt%	Symbol	R Phrases
Distillate (petroleum) hydro treated light	64742-47-8	10-20%	Xn	65, 66
		EC 265-149-8		
Cobalt zirconium carboxylate 38,43		<0.5%	Xi	
Methyl ethyl ketoxime		<0.5%	Xn	21,40,41,43

3 HAZARDS IDENTIFICATION: Non hazardous in normal use.

4 FIRST AID MEASURES:

- 4.1 General Advice: Remove contaminated clothing. Launder before re-use.
- 4.2 Inhalation: Remove to fresh air.
- 4.3 Eye Contact: Rinse with copious amounts of water and seek immediate medical attention.
- 4.4 Skin Contact: Remove surplus material, then wash with soap and water.
- 4.5 Ingestion: Rinse out mouth with water. Do not induce vomiting. Consult a doctor.

5 FIRE PRECAUTIONS:

- 5.1 Extinguishing Media: CO₂, foam, dry chemical
- 5.2 Extinguishing Media NOT to be used: Water
- 5.3 Product Combustion Hazards: Smoke, CO, CO₂
- 5.4 Special Protective Equipment for Firefighters: -

6 SPILLAGE:

- 6.1 Personal Precautions: Avoid skin and eye contact.
- 6.2 Environmental Precautions: -
- 6.3 Removal of Spillage: Absorb in earth or sand and transfer to suitable container for disposal.
- 6.4 Further Advice: -

7 HANDLING & STORAGE:

- 7.1 Safe Handling: It is recommended that gloves and safety goggles are worn.
- 7.2 Safe Storage: Store in closed containers in dry, cool conditions.

PRODUCT: SATIN OIL GOLD

PAGE: 2/3

REVISION (2): 05/08/03

8 PERSONAL PROTECTION:

- 8.1 Respiratory Protection: Ensure good ventilation in working areas.
- 8.2 Hand Protection: Solvent resistant gloves. Seek advice from glove suppliers and follow their advise.
- 8.3 Eye Protection: Safety glasses recommended.
- 8.4 Skin Protection: Industrial footwear.

9 PHYSICAL & CHEMICAL PROPERTIES:

- 9.1 Appearance: Liquid
- 9.2 Odour: Mild
- 9.3 Colour: Straw
- 9.4 Boiling Point/Range: >200 C
- Flash Point: 101 C
- Auto Ignition Temp: -
- Oxidising Properties: -
- Relative Density: <1.0
- Melting Point/Range: -
- Flammability(solid, gas): -
- Explosive Limits: -
- Vapour Pressure: -
- Water Solubility: Insoluble
- Solvent Content: 20%
- Viscosity: approx 40 CSt @ 40° C

10 STABILITY & REACTIVITY:

- 10.1 Conditions to avoid: Heat, sources of ignition
- 10.2 Materials to avoid: Oxidising agents
- 10.3 Hazardous Decomposition Products: CO, CO₂, smoke

11 TOXICOLOGICAL INFORMATION:

There is no data on the product itself. The product has been assessed following the conventional method in CHIP and is classified for toxicological effects accordingly. See sections 3 & 15.

12 ECOLOGICAL INFORMATION:

Prevent contamination of soil, drains or surface water. This preparation has been assessed following the conventional method in CHIP and is not classified as dangerous for the environment.

13 SAFE DISPOSAL:

- 13.1 Product: Dispose of by controlled incineration.
- 13.2 Container: Dispose of by controlled incineration.

PRODUCT: SATIN OIL GOLD

PAGE: 3/3

REVISION (2): 05/08/03

14 TRANSPORT INFORMATION: Not classified as hazardous for transport

15 REGULATORY INFORMATION: Not classified as hazardous for supply.

Other Data: -

Contains methyl ethyl ketoxime and cobalt zirconium carboxylate. May cause an allergic reaction.

16 OTHER INFORMATION: Under certain conditions, applicators, cloths, sawdust, etc., impregnated with this product can spontaneously combust. To prevent the possibility of spontaneous combustion impregnated applicators, cloths, sawdust, etc., should be immediately placed in a metal container filled with water, sealed and placed outside the building. The container should then be disposed of according to local regulations.

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation. It provided guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.