

# **TIMBEREX INTERNATIONAL LIMITED**

**WATCO HOUSE, FILMER GROVE, GODALMING, SURREY GU7 3AL**

**TEL: 01483 425 000 FAX: 01483 428 888**

## **MATERIAL SAFETY DATA SHEET**

**PAGE: 1/ 3**

**REVISION (2): 20/10/05**

**1 PRODUCT NAME: Softwood Lut Coloured**

**2 CHEMICAL COMPOSITION:**

	CAS No.	Wt%	Symbol	R Phrase
Sodium Hydroxide	1310-73-2	<2%	C	35

**3 HAZARDS IDENTIFICATION: Irritating to eyes and skin.**

**4 FIRST AID MEASURES:**

- 4.1 General Advice: Treat symptomatically.
- 4.2 Inhalation: Remove patient to fresh air. Seek medical advice.
- 4.3 Eye Contact: Flush with water. Seek immediate medical advice.
- 4.4 Skin Contact: Rinse with water. In case of burns seek medical advice.
- 4.5 Ingestion: Seek medical attention. Do not induce vomiting.

**5 FIRE PRECAUTIONS:**

- 5.1 Extinguishing Media: Not flammable.
- 5.2 Extinguishing Media NOT to be used: -
- 5.3 Product Combustion Hazards: Can react with some metals to produce hydrogen gas.
- 5.4 Special Protective Equipment for Firefighters:-

**6 SPILLAGE:**

- 6.1 Personal Precautions: Waterproof gloves, overalls and eye protection.
- 6.2 Environmental Precautions: -
- 6.3 Removal of Spillage: Absorb spills into dry sand or other absorbent material, for disposal. Residues should be flushed away with plenty of water.
- 6.4 Further Advice: Floor area may be slippery.

**7 HANDLING & STORAGE:**

- 7.1 Safe Handling: -
- 7.2 Safe Storage: Store in a closed container at ambient temperature.

**8 PERSONAL PROTECTION:**

- 8.1 Respiratory Protection: Not required
- 8.2 Hand Protection: Impervious gloves.
- 8.3 Eye Protection: Safety glasses.
- 8.4 Skin Protection: Impervious overalls to prevent repeated or prolonged contact.

**9 PHYSICAL & CHEMICAL PROPERTIES:**

- 9.1 Appearance: Liquid
- 9.2 Odour: -
- 9.3 Colour: As described.
- 9.4 Boiling Point/Range: -
- Flash Point: -
- Auto Ignition Temp: -
- Oxidising Properties: -
- Relative Density: 1.4 to 1.1
- Melting Point/Range: -
- Flammability (solid, gas): -
- Explosive Limits: -
- Vapour Pressure: -
- Water Solubility: Soluble
- Other Data: -
- Solvent Content: Nil

**10 STABILITY & REACTIVITY:**

- 10.1 Conditions to avoid: Normally stable.
- 10.2 Materials to avoid: Evolves hydrogen in contact with aluminium and zinc.  
Violent reaction with acids.
- 10.3 Hazardous Decomposition Products: Hydrogen.

**11 TOXICOLOGICAL INFORMATION:**

- 11.1 Toxicity: LD50 Oral: 1000mg/kg, rat.
- LD50 Skin: -
- Skin Irritation: -
- Sensitisation: -
- Inhalation: -
- Recommended Exposure Limit: -

**PRODUCT: SOFTWOOD LUT COLOURED**

**PAGE: 3/3**

**REVISION (2): 20/10/05**

**12 ECOLOGICAL INFORMATION:**

High pH value has a potential to damage soil structure.  
Toxic to aquatic organisms.  
Can cause long term adverse effects in the aquatic environment.

**13 SAFE DISPOSAL:**

13.1 Product: Dispose of with respect to National and local Byelaws.

13.2 Container: Dispose of with respect to National and local Byelaws.

**14 TRANSPORT INFORMATION:**

NOT CLASSIFIED AS HAZARDOUS

**15 REGULATORY INFORMATION:**

IRRITANT

Xi

*R phrases*

36/38: Irritating to eyes and skin.

*S phrases*

2: Keep out of reach of children.

26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

37/39: Wear suitable gloves and eye/face protection.

45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

**16 OTHER INFORMATION:**

-